


# METÁLICOS MEDELLÍN

EN ACERO, SURTIDO, PRECIO Y SERVICIO...EL MEJOR

## HOJA TÉCNICA DE PRODUCTO

### VIGA I.P.S.



#### Propiedades

peralte		peso kg/m	área cm <sup>2</sup>	Eje X-X			Eje Y-Y		
pulg	mm			I cm <sup>4</sup>	r cm	s cm <sup>3</sup>	I cm <sup>4</sup>	r cm	s cm <sup>3</sup>
3	76.2	8.49	10.52	103.30	3.12	27.1	19.1	1.35	6.5
4L	100.0	8.34	10.60	171.00	4.01	34.2	12.2	1.07	4.8
4	101.6	11.46	14.26	249.30	4.17	48.9	32.1	1.50	9.5
5	127.0	14.88	18.52	503.30	5.21	79.3	52.1	1.65	13.4
6	152.4	18.6	23.29	906.80	6.25	119.0	77.0	1.83	18.2
7	177.8	22.78	28.90	1506.80	7.26	169.5	112.3	1.98	24.2
8	203.2	27.38	34.39	2367.20	8.31	233.0	157.3	2.13	31

pulg	mm	kg/m	patin		alma			distancia			A	gra mil G	diam. Max. remaches o tornillos
			ancho	espesor	espesor	medio	tangente	F	E	F			
			B	D	C	espesor C/2	T						
3.0	76.2	8.5	59.0	6.6	4.3	2.0	45.0	15.5	38.0	12.0	27.0	36.0	9.5
4.0	101.6	11.5	68.0	7.4	4.8	3.0	70.0	16.0	50.0	13.0	32.0	38.0	12.7
5.0	127.0	14.9	76.0	8.3	5.3	3.0	89.0	19.0	64.0	13.0	35.0	40.0	12.7
6.0	152.4	18.6	85.0	9.1	5.8	3.0	114.0	19.0	72.0	13.0	40.0	44.0	15.8
8.0	203.2	27.4	102.0	10.8	6.9	4.0	159.0	22.0	76.0	14.0	48.0	56.0	19.0